



Shell Helix *Top Up* Oil 0W-30

Fully Synthetic Motor Oil - Designed for Ultimate Engine Performance

Shell Helix Top Up 0W-30 is suitable as top-up oil for modern gasoline engines and diesel engines with particulate filters.

Main Applications

- Shell Helix Top Up 0W-30 is suitable for modern gasoline and diesel engines.
- It is suitable for use in vehicles currently using SAE 5W-30 or 10W-30 oils, providing the same standard of protection together with enhanced fuel economy*.

* Compared to oils meeting API SN or ACEA C2 or C3 performance standards.

Specifications, Approvals & Recommendations

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at:
<http://lubematch.shell.com>

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Helix Top Up Oil 0W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	11.85
Kinematic Viscosity	@40°C	cSt	ASTM D445	58.65
Viscosity Index			ASTM D2270	205
MRV Viscosity	@-40°C	cP	ASTM D4684	18 700
Density	@15°C	Kg/m ³	ASTM D4052	837
Flash Point		°C	ASTM D92	226
Pour Point		°C	ASTM D97	-51

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.